


Panel	15.55" TFT LCD (16:9 Wide) LED Backlight			Plug & Play	Support VESA DDC2 °	
Resolution	1366 x 768 (262K colors)			Dimension (W/H/T) & Weight (Without Protection Cover) : 2501M 387 mm x 260 mm x 12.8 mm; 1088g (2501A:893g)		
Active Area	344.2mm x 193.5mm					
Viewing Angle	(U/D/R/L) 20°/45°/45°/45° (Typical)			Dimension (W/H/T) & Weight (With Protection Cover) : 2501M 395 mm x 260 mm x 16.3 mm ; 1,312g (1,117g)		
Brightness	200 (cd/m2) (Typical)					
Contrast Ratio	400:1(Typical)			Package and Accessories		
Response Time	8 (ms) (Typical) /16(ms) (Max.)			Protection Cover * 1	5V DC Charger*1(5V,Max.2A )	
Resolutions of Video Input	MAC	640x480	XGA	1024x768	Micro HDMI cable *1	Phone Holder Set *1 (Optional)
	VESA	720x400	WXGA	1366x768	MHL cable *1 (Not Available in 2501A)	Stand Brick*2
	SVGA	800x600			VGA cable*1	Cable Click*1
Connectivity	HDMI		Audio Jack		Micro USB Power cable *1	User manual*1;Q.I.G.*1
	MHL(Mobile High Link)(Not Available in 2501A)				Package Dimension & Weight	
	D-sub (VGA) (Optional VGA Cable)				Color Box Dimension:	451mmx329mmx64mm
Speakers	2x 1.0W(Max.) (Rated Impedance 8Ω at 2KHz)			Gross Weight(Color Box):	2501M: 2.39Kg ; 2501A:2.11Kg	
Battery	9300 mAH (Not Available in 2501A)			Carton Dimension(5pcs):	479mmx367mmx357mm	
	(Lithium ion polymer rechargeable battery)			Gross Weight(Carton):	2501M: 13.26Kg ; 2501A:11.87Kg	
Rating Voltage	5V  DC			Charge Time	6 Hour	
Rating Current	Brightness	Audio Volume	Battery Time			
1350 mA	100%	10	7 Hour*		*Battery time is affected by audio input. Larger audio input results in shorter battery time.	
1000 mA	50%	10	10 Hour*			